



Effective 28 October, 2005

3871S

THINNER

Description

Solvent mixture developed to remove mould release and other surface contaminants from plastics.

Composition based on blend of aromatic and alcohol solvents.

Products

3871S DuPont™ Thinner

Auxiliary products

DP3330 DuPont™ Marine Finishes Spray Fairing

DP8130 DuPont™ Marine Finishes Alu Grip Primer

DP8140 DuPont™ Marine Finishes Universal Primer

Properties

- Eliminates non-water soluble contaminants, such as mould release agents and removes small amounts of grease and oil.
- Can also be used as thinner for DP3330 and for DP8130 and DP8140 epoxy primers (see specific TDS).

Substrates

Most exterior plastic parts.



Effective 28 October, 2005

3871S

THINNER

RECOMMENDED USE

Application - remarks

Following specifications listed in the DuPont™ Marine Finishes Manual and in particular:

- Clean surface with water and soap.
- Wipe dry with clean cloth or blow dry with air.
- Degrease with 3871S.
- Wipe surface to loosen and lift contaminants. Immediately, thoroughly wipe off with a clean cloth.
- Close container after use. This prevents the cleaner to evaporate and to lose strength.

Products	Packages (l)	Storability at 20°C (year)	VOC (g/l)	Density (kg/l)
3871S	5	2	840	0.839
DP3330	5	2		1.408
DP8130	3.55	2		1.137
DP8140	3.5	2		1.225

Safety

Consult Material Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.