



Effective 28 October, 2005

3919S

PREPSOL

Description

Slow solvent mixture developed for removal of heavy contaminants prior to surface preparation. Composition based on aromatic and aliphatic solvents.

Products

3919S DuPont™ Prepsol

Auxiliary products

3920S DuPont™ Degreaser

Properties

- Eliminates non-water soluble contaminants, such as wax, polish, tar, silicones and grease from old finishes.

Application - remarks

Following specifications listed in the DuPont™ Marine Finishes Manual and in particular:

- Never let 3919S evaporate from the surface. Treat only one small area at the time.
- Change cloths often; never use dirty cloths. It is important to thoroughly clean the surface before any sanding operation. Sanding would grind the contaminants into the surface.
- Never clean uncoated bare metal with 3919S. For spot repair sand throughs use 3920S (see specific TDS).



Effective 28 October, 2005

3919S

PREPSOL

RECOMMENDED USE

Products	Packages (l)	Storability at 20°C (year)	VOC (g/l)	Density (kg/l)
3919S	5 - 20	2	809	0.811
3920S	5 - 20	2	776	0.776

Safety

Consult Material Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.