

SAFETY DATA SHEET



REG EUADD0

Product: **DP8145 DUPONT(TM) MARINE FINISHES UNIVERSAL PRIMER ACTIVATOR**

Print Date: 02.05.2005

Version: 1.0

Revision Date: 02/05/2005

Page: 1/6

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation

- Commercial Product Name: DP8145 DUPONT(TM) MARINE FINISHES UNIVERSAL PRIMER ACTIVATOR

- Intended use of the substance/preparation: Coating for professional use

Manufacturer, importer, supplier

- Producer/Supplier: Du Pont de Nemours (Belgium)
- Street/Box: A. Spinoystraat 6
- Nat.-Code/Postal code/City: B-2800 MECHELEN
- Telephone: +32-(0)15-44.10.11
- Responsible Department: Regulatory Affairs
- Telephone: ++49 (0)202 529 2385
- Emergency telephone: +35236666543, +31(0)786301899

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization of the product

- Description: Mixture of synthetic resins and solvents

- Hazardous components:

Substances presenting a health or environmental hazard within the meaning of the DSD 67/548/EEC incl. 28. ATP

EINECS-No.	CAS-No.	Chemical Name	Concentration	Classification
215-535-7	1330-20-7	xylene	25,00 - < 50,00 %	R10 Xn; R20/21 Xi; R38
202-849-4	100-41-4	ethylbenzene	10,00 - < 12,50 %	F; R11 Xn; R20
202-013-9	90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	3,00 - < 5,00 %	Xn; R22 Xi; R36/38
200-661-7	67-63-0	propan-2-ol	3,00 - < 5,00 %	F; R11 Xi; R36 R67
265-185-4	64742-82-1	white spirit	1,00 - < 2,00 %	Xn; R65

- Additional advice:
See full text of R-phrases in chapter 16.

3. HAZARDS IDENTIFICATION

The product is classified as dangerous in accordance with Directive 1999/45/EC.

- Human health hazards:

Classification : - flammable - irritant - harmful

Flammable. Irritating to skin. Harmful by inhalation and in contact with skin.

4. FIRST AID MEASURES

- General advice:

When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.

- Inhalation:

Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

- Skin contact:

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser.

- Eye contact:

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Seek medical advice.

- Ingestion:

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do not induce vomiting.

SAFETY DATA SHEET



REG EUADD0

Product: **DP8145 DUPONT(TM) MARINE FINISHES UNIVERSAL PRIMER ACTIVATOR**

Print Date: 02.05.2005

Version: 1.0

Revision Date: 02/05/2005

Page: 2/6

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media:
alcohol-resistant foam, carbon dioxide (CO₂), dry powder, water spray
- Extinguishing media which must not be used for safety reasons:
high volume water jet
- Special exposure hazards from the product itself, combustion products, resulting arising gases:
Fire will produce dense black smoke containing hazardous combustion products (see heading 10).
Exposure to decomposition products may be a hazard to health.
- Special protective equipment for fire-fighters:
Respiratory protective device may be required.
- Additional advice:
Cool closed containers exposed to fire with water spray.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:
Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Air out the room. Do not inhale vapours.
- Environmental precautions:
Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.
- Methods for cleaning up:
Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

7. HANDLING AND STORAGE

Handling

- Safe handling advice:
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spraybooth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. Particularly for spray mist the sustained certain compliance with the limitation on respirable dust is improbable. Particularly for spray mist compliance with the limitation on respirable dust is improbable.
- Advice on protection against fire and explosion:
Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Storage

- Requirements for storage areas and containers:
Keep containers tightly closed. Never use pressure to empty container: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Advice on common storage:
Keep away from oxidising agents and strongly acid or alkaline materials.
- Additional information on storage conditions:
Always keep in containers of same material as the original one. Observe label precautions. Place away from sources of heat and direct sunlight. Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Additional technical information on the plant

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

SAFETY DATA SHEET



REG EUADD0

Product: **DP8145 DUPONT(TM) MARINE FINISHES UNIVERSAL PRIMER
ACTIVATOR**

Print Date: 02.05.2005

Version: 1.0

Revision Date: 02/05/2005

Page: 3/6

Exposure limit values

CAS-No.	Chemical Name	Type	Value	Note
1330-20-7	xylene	STEL	150,00 ml/m3	1
		TWA	100,00 ml/m3	
100-41-4	ethylbenzene	STEL	125,00 ml/m3	
		TWA	100,00 ml/m3	
67-63-0	propan-2-ol	TWA	200,00 ml/m3	
		STEL	400,00 ml/m3	

- Additional advice:
(A.C.G.I.H. Treshold Limit Values) 2003.

Exposure controls

- Respiratory protection:
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

- Hand :

	Glove material	Glove thickness	Break through time
xylene	nitrile rubber	0,33 mm	30 minute
	Viton	0,7 mm	480 minute
white spirit	nitrile rubber	0,33 mm	30 minute
	Viton	0,7 mm	480 minute

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in chapter 2 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Cleaning solvents or viscosity adjustment thinners require special hand protection, a fluorocarbon rubber glove should be used. Solvents are to be used only for adjusting the viscosity. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately. Preventive skin protection such as skin protective cream is recommended. Work tasks should be arranged in such a way that gloves do not have to be worn continuously.

- Eye protection:
Wear protective eyewear for protection against solvent spatter.
- Skin protection:
Personnel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber.
- Protective measures / Hygiene measures:
Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

Environmental exposure controls

Do not let product enter drains.
For ecological information refer to chapter 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information (appearance)

Physical state: liquid Colour: colourless

¹ Note:

H: Skin resorbitive

Y: There is no need to fear risk of fetal damage if complying with the MWC and the BWST values.

SAFETY DATA SHEET



REG EUADD0

Product: **DP8145 DUPONT(TM) MARINE FINISHES UNIVERSAL PRIMER
ACTIVATOR**

Print Date: 02.05.2005

Version: 1.0

Revision Date: 02/05/2005

Page: 4/6

Important health, safety and environmental information

	Value	Method
- Flash point:	32 °C	ISO 1523
- Lower explosion limit (Vol.):	1,0 %(V)	
- Upper explosion limit (Vol.):	8,1 %(V)	
- Relative density (20 °C):	0,99 g/cm3	
- Water solubility:	insoluble	
- Viscosity (23 °C):	>= 60 s	ISO 2431-1993 6,0 mm
- Solvent separation test:	<3%	ADR/RID
- Content of volatile components:	46 %	

10. STABILITY AND REACTIVITY

- Conditions to avoid:
Stable under recommended storage and handling conditions (see section 7).
- Materials to avoid:
Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Hazardous decomposition products:
When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

Practical experience

- Further observations:
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.
Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.
The liquid splashed in the eyes may cause irritation and reversible damage.
Through skin resorption, solvents can cause some of the effects described here.

General observations

There are no data available on the product itself. See sections 2 and 15 for details.

12. ECOLOGICAL INFORMATION

- Acute toxicity aquatic invertebrates :
- Acute and extended toxicity of fishes :
- Toxicity with aquatic plants :
- Toxicity with micro organisms :

Mobility

no data available

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Other adverse effects

The preparation was evaluated in accordance with the conventional method of the preparation directive 1999/45/EG and was not classified as environmentally dangerous.

Additional ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses. Do not let product enter drains.

13. DISPOSAL CONSIDERATIONS

Product

- Recommendation:
The conversion into energy disposal process is recommended. To the extent not possible only the hazardous waste incineration is suitable.
- Catalogue Code:
Catalogue Code: _____ Description: _____

SAFETY DATA SHEET



REG EUADD0

Product: **DP8145 DUPONT(TM) MARINE FINISHES UNIVERSAL PRIMER
ACTIVATOR**

Print Date: 02.05.2005

Version: 1.0

Revision Date: 02/05/2005

Page: 5/6

080111

Waste from paint and varnish containing organic solvents or other dangerous substances

Uncleaned packaging

- Recommendation:
Properly emptied containers are to be scrap processed or reconditioned. Improperly emptied containers are considered hazardous waste (waste key number 150110).

14. TRANSPORT INFORMATION

Transport only in accordance with the requirements of the Carriage of Dangerous Goods by Road and Rail (Classification, Packaging and Labeling), ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

Land transport

ADR/RID :

- Class: 3
- UN-No: 1263
- Description of the goods: PAINT
- Packing group: III
- Release of danger:

Sea transport

IMDG:

- Class: 3
- UN-No: 1263
- EmS: 3-05
- Marine pollutant: NO

- Proper technical name: PAINT
- Packing group: III
- Release of danger:

Air transport

ICAO/IATA:

- Class: 3
- UN/ID No.: 1263
- Proper technical name: PAINT
- Packing group: III
- Release of danger:

15. REGULATORY INFORMATION

In accordance with the CHIP Regulations 2002 the product is labelled as follows:

- Symbol and indicating of hazard:
Xn Harmful

Contains: xylene
- R-phrases(s):
R10 Flammable.
R20/21 Harmful by inhalation and in contact with skin.
R38 Irritating to skin.
- S-phrases(s):
S23 Do not breathe vapour.
S36/37 Wear suitable protective clothing and gloves.
S38 In case of insufficient ventilation, wear suitable respiratory equipment.

- Other directives, limitations and prohibitory regulations:
Restricted to professional users.

16. OTHER INFORMATION

Full text of R phrases with no. appearing in section 2:

- R10 Flammable.
- R11 Highly flammable.
- R20 Harmful by inhalation.

SAFETY DATA SHEET



REG EUADD0

Product: **DP8145 DUPONT(TM) MARINE FINISHES UNIVERSAL PRIMER
ACTIVATOR**

Print Date: 02.05.2005

Version: 1.0

Revision Date: 02/05/2005

Page: 6/6

R20/21	Harmful by inhalation and in contact with skin.
R22	Harmful if swallowed.
R36	Irritating to eyes.
R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

Further information

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.